



RHODES
ARCHITECTURAL
STONE
NATURAL STONE EXPERTS

NEW YANGTZE LIMESTONE

A high-density limestone, New Yangtze Limestone is quarried in the Yangtze River Valley near the source of its ancient relative, Antique Yangtze Limestone, so they blend seamlessly in projects. Yet New Yangtze Limestone is darker and more consistent in color with small crystalline inclusions and occasional white veins.

Ancient fossils visible throughout the stone confirm the natural history and variation to the final product.

Its true beauty appears through the light tooling marks of our hand finishes, which accentuate the deep chocolate tones of this eye-catching stone.

The popularity of New Yangtze Limestone is based on its multiple applications. It is particularly striking in oversized architectural elements such as lintels, sills and stair blocks and works equally well on all pavements being much cooler underfoot than sandstone or granite.



RECOMMENDED USES

PAVERS	SILLS / LINTELS
VENEER	CARVED OBJECTS
STAIR BLOCKS	COLUMNS
QUOINS	SINKS / TUBS
COPING / CAPS	SLABS
CURBS	COBBLESTONES

PROJECTS

Colorado Ranch, Locksley Hall,
Mercy Hospital, Westerleigh Residence

INSTALLATION

It may be mortar set as its strong, primary grain can cause edges to chip under pressure. For veneer, it may be mortar set with an exposed or raked joint or set more tightly in the wedge mortar method.



UNITED STATES OF AMERICA
TEL +1 206 709 3000

rhodes-stone.com
info@rhodes-stone.com

AUSTRALIA
TEL +61 3 8199 9555

CHINA
TEL +86 592 533 0273



NEW YANGTZE LIMESTONE



HONED
min thickness - 0.75" / 20 mm



FLAMED
min thickness - 1.25" / 32 mm



BUSH HAMMER
min thickness - 1.5" / 38 mm



FINE ADZE
min thickness - 1.5" / 38 mm



COARSE ADZE
min thickness - 2" / 50 mm



4 POINT STALK
min thickness - 1.25" / 32 mm



2 POINT STALK
min thickness - 1.25" / 32 mm



PINEAPPLE
min thickness - 3" / 75 mm



SPLIT
min thickness - 3" / 75 mm



MATERIAL SPECIFICATIONS

STANDARD BLOCK : 60" x 24" x 18"

1500 x 600 x 450 mm

MAX SPECIAL BLOCK : 100" x 20" x 13"

2500 x 500 x 330 mm

STANDARD VENEER : 3" x 8" to 16" x 26"; 2" - 3" thick

75 x 200 mm to 400 x 650 mm; 50 - 75 mm thick

STANDARD PAVERS :

12" x 12" to 24" x 30"; 1.25" - 3" thick

4" x 4"; 2.5 - 4" thick cobblestones

8" x 4"; 2.5 - 4" thick cobblestones

300 x 300 mm to 600 x 750 mm; 30 - 75 mm thick

100 x 100 mm; 64 - 100 mm thick cobblestones

200 x 100 mm; 64 - 100 mm thick cobblestones



TECHNICAL DATA

ASTM	TEST	
C666	freeze thaw	0.015 %
C97	absorption	0.07 %
C97	bulk gravity	169 lbs/ft ³ 2,711 kg/m ³
C99	mod. of rupture	1,421 psi 9.8 MPa
C170	compressive strength	25,230 psi 174 MPa
C880	flexural strength	1,175 psi 8.1 MPa
C241	abrasion resistance	22 Ha

UNITED STATES OF AMERICA
TEL +1 206 709 3000

rhodes-stone.com
info@rhodes-stone.com

AUSTRALIA
TEL +61 3 8199 9555

CHINA
TEL +86 592 533 0273