



NIGHTLIGHT GRANITE



HONED
 min thickness - 0.75" / 20 mm



SANDBLASTED
 min thickness - 0.75" / 20 mm



FLAMED
 min thickness - 0.75" / 20 mm



BUSH HAMMER
 min thickness - 1.5" / 38 mm



FINE ADZE
 min thickness - 1.5" / 38 mm



COARSE ADZE
 min thickness - 2" / 50 mm



SPLIT
 min thickness - 3" / 75 mm

MATERIAL SPECIFICATIONS

STANDARD BLOCK : 60" x 35" x 26"
 1525 x 900 x 650 mm

OVERSIZED BLOCK : 79" x 39" x 26"
 2000 x 1000 x 650 mm



TECHNICAL DATA

ASTM	TEST	
C97	absorption	0.05 %
C97	bulk gravity	187 lbs/ft ³ 3,000 kg/m ³
C99	mod. of rupture	2,582 psi 17.8 MPa
C170	compressive strength	34,229 psi 236 MPa
C880	flexural strength	2,872 psi 19.8 MPa

UNITED STATES OF AMERICA
 TEL +1 206 709 3000

AUSTRALIA
 TEL +61 3 8199 9555

CHINA
 TEL +86 592 533 0273

rhodes-stone.com
info@rhodes-stone.com